## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

# (19) World Intellectual Property Organization

International Bureau



# 

#### (43) International Publication Date 15 July 2004 (15.07.2004)

PCT

### (10) International Publication Number WO 2004/059041 A1

(51) International Patent Classification<sup>7</sup>: 5/50, 5/34, 5/10, C23C 28/00

C25D 3/48,

(21) International Application Number:

PCT/US2002/041667

(22) International Filing Date:

20 December 2002 (20.12.2002)

(25) Filing Language:

English

(26) Publication Language:


English

- (71) Applicant (for all designated States except US): MID-WEST RESEARCH INSTITUTE [US/US]; 425 Volker Boulevard, Kansas City, MO 664110 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): BHATTACHARYA, Raghu, Nath [US/US]; 5573 South Taft Street, Littleton, CO 80127 (US). CHEN, Jun [CN/US]; 32 South Holman Way, #3A, Golden, CO 80401 (US).

- (74) Agents: WHITE, Paul, J. et al.; National Renewable Energy Laboratory, 1617 Cole Boulevard, Golden, CO 80401 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

#### (54) Title: ELECTRODEPOSITION OF BIAXIAL TEXTURED FILMS



(57) Abstract: The present invention provides a method of forming a biaxially textured gold buffer layer (14) on a substrate(16) by electrodeposition. A superconducting material (12) may be deposited onto the biaxially textured goldlayer (14). The biaxial texturing in the gold layer (14) is maintained in the deposited superconductor material(12) to produce high critical current density.

WO 2004/059041 A1